



C o u n t y o f S a n L u i s O b i s p o
GENERAL SERVICES AGENCY

Janette D. Pell, Director

Helen McCann, Department Administrator

**INVITATION TO BID #3554-11
NEW AND UNUSED DUMP TRUCK**

December 12, 2011

The County of San Luis Obispo is currently soliciting bids for a New and Unused Dump Truck as noted.

Each bid shall specify each and every item as set forth in the attached specifications. Any and all exceptions must be clearly stated in the bid. Failure to set forth any item in the specifications shall be grounds for rejection. The County of San Luis Obispo reserves the right to reject all bids and to waive any informalities.

Please submit your bids on the attached form. They must be received at the office of the General Services Department **no later than 3:00 p.m. on January 4, 2012.**

All questions pertaining to the content of this Invitation to Bid must be made in writing via e-mail to Barbara Adams at: beadams@co.slo.ca.us. All questions will receive a response within five (5) business days. The question and its response will be posted (anonymously) on the County's Purchasing web site located at: http://www.slocounty.ca.gov/GSA/Purchasing/Current_Formal_Bids_and_Proposals.htm. The County reserves the right to determine the appropriateness of comments/questions that will be posted on the website.

Any and all comments and suggestions are sincerely encouraged prior to the bid opening.

Barbara Adams
Buyer – GSA-Purchasing
beadams@co.slo.ca.us

**County of San Luis Obispo Invitation to Bid #3554-11 December 12, 2011 Page 2
NEW AND UNUSED DUMP TRUCK**

TO: ALL PROSPECTIVE BIDDERS
SUBJECT: LOCAL BIDDERS PREFERENCE

The County of San Luis Obispo has established a local vendor preference. All informal and formal bids for contracts will be evaluated with a 5% preference for local vendors. Note the following exceptions:

1. Those contracts which State Law requires be awarded to the lowest responsible bidder.
2. Public works construction projects.

A "local" vendor will be approved as such when, 1) It conducts business in an office with a physical location within the County of San Luis Obispo; 2) It holds a valid business license issued by the County or a city within the County; and 3) Business has been conducted in such a manner for not less than six (6) months prior to being able to receive the preference.

As of March 3, 1994 individual County Buyers evaluate bids considering the local vendor preference described above. The burden of proof will lie with bidders relative to verification of "local" vendor preference. Should any questions arise, please contact a buyer at (805) 781-5200. All prospective bidders are encouraged to quote the lowest prices at which you can furnish the items or services listed in County bids.

	YES	NO
Do you claim local vendor preference?		
Do you conduct business in an office with a physical location within the County of San Luis Obispo?		
Business Address: _____ _____		
Years at this Address: _____		
Does your business hold a valid business license issued by the County or a City within the County?		
Name of Local Agency which issued license: _____		

Business Name: _____

Authorized Individual: _____ Title: _____

Signature: _____ Dated: _____

TO: ALL PROSPECTIVE BIDDERS

**SUBJECT: POLICY ON PURCHASING PRODUCTS MADE WITH OR CONTAINING
CHLOROFLUOROCARBONS (CFC's)**

Summary

Many products contain chlorofluorocarbons (CFC's), a known depleter of ozone in the atmosphere. Under the U.S. Clean Air Act and the Montreal Protocol on Substances That Deplete the Ozone Layer, CFC production for use in industrialized nations is to be totally phased out by January 1, 1996. There are still many products on the market that contain CFC's or are made with CFC's. The Department of General Services, purchasing staff must identify products made with or containing CFC's and purchase alternative products whenever practical and possible.

Policy

To this end, it shall be the policy of the County of San Luis Obispo that all bidders, who wish to do business with the County are required to identify all products that contain CFC's or use CFC's in the manufacturing or shipping processes. Bidders are required to identify alternative products that do not use CFC's, for possible purchase by the County.

Bidder Response

	YES	NO
Do any products offered herein contain CFC's or use CFC's in the manufacturing or shipping process?		
If yes, please offer an alternative product by copying bid forms and submitting an alternate bid. Will you offer an alternate?		
Please provide any other information that may be helpful to the County. Attachments are acceptable.		

Bidder: _____

GENERAL CONDITIONS AND INSTRUCTIONS

1. All bids submitted by Seller to Purchaser should be submitted upon the attached bidder's form, completed and signed, (only typewritten or ink shall be accepted with no erasures or corrections unless properly authenticated by signature) in accordance with the instructions contained herein.
2. The issuance of this bid request creates no obligation on the part of the County and the County reserves the unconditional right at its option to either reject all bids or waive any irregularities or informalities therein. Each bid shall be in a separate sealed envelope with the bid number, name of bidder, title of the bid, date and time due showing on the outside of the envelope.
3. All prices must be firm for 45 days from the date of the bid opening and be inclusive. Upon award, prices will be in effect for the term of the contract.
4. If you offer any prompt payment discounts, please indicate this on your bid.
5. Awards will be made to realize the greatest savings to the County and may not necessarily be the lowest bid especially where services are of the utmost importance.
6. Submission of a signed bid will be interpreted to mean that the bidder has thereby agreed to all conditions, instructions, descriptions and specifications contained herein.
7. All materials included in the contract shall be in compliance with all Federal and State OSHA laws.
8. All applicable City, State, and Federal taxes and fees are to be included in the proposal.
9. The only terms that will be honored are those terms included in general and special conditions and instructions, purchase order or other documents issued by the County.
10. In the event of any conflicts or ambiguities between these instructions and State or Federal laws, regulations or rules, then the latter shall prevail.
11. Only one bid will be accepted per vendor.
12. Bidders may withdraw their bid either personally, by written request, or by telegraphic request confirmed in the manner specified above at any time prior to the scheduled closing time for receipt of bids. No bidder may withdraw their bid after the time set for the opening.
13. All time limits stated are of the essence and must be complied with. Any bids received after closing time stipulated will be returned unopened.
14. All bids must be submitted in a manner so they can be readily hole-punched and placed in a standard legal size file folder.

15. The County may make partial payments after a substantial portion of the merchandise has been delivered. On all items, a 10% retention will be withheld until all merchandise has been accepted.
16. Brand names are used to establish a level of quality only. Any alternates must be approved five (5) days prior to the bid opening date, by the Central Services Manager, who will have the sole right to determine this. If an alternate is submitted without going through the above-described process, the County will have the sole right to decide whether or not an alternate is acceptable.
17. Vendor agrees that it will not discriminate against any employee or applicant for employment because of race, color, religion, sex or national origin and that it will comply with the "Contractor's Agreements" provisions of Presidential Executive Order No. 11246.
18. **NO FAXED** Bids will be accepted.
19. Return bid by **January 4, 2012 at 3:00 p.m.** to:

COUNTY OF SAN LUIS OBISPO
GENERAL SERVICES AGENCY
BARBARA ADAMS, BUYER
1087 SANTA ROSA STREET
SAN LUIS OBISPO, CALIFORNIA 93408

SPECIAL TERMS, CONDITIONS AND INSTRUCTIONS

It is the intent of these specifications to describe a New and Unused 15 yard Dump Truck equivalent in style, quality and appointments to those offered of standard manufacture. The vehicle shall be supplied with all new equipment and accessories indicated as standard equipment in the manufacturer's published literature. All equipment/options are to be factory installed. If some equipment/options are not available from the factory, dealer installation may be acceptable if specified as dealer installed in the bid response and accepted by the County.

1. Deviations: The specifications describe minimum or average requirements. Minor deviations from specifications may be acceptable provided that the operating capacities or characteristics of the vehicles are not adversely affected. Such deviations are to be submitted in writing with the bid submission and the County reserves the right to make the final determination as to whether or not any deviations are acceptable.
2. Regulations: All equipment and accessories shall meet OSHA, Department of Industrial Safety and California Highway Patrol regulations. The following regulations are a partial listing of regulations which may be in effect at the closing of the bid are incorporated to the extent applicable. Seller is responsible for ensuring that the vehicles offered meet all applicable laws including but not limited to:
Department of Transportation, Federal Highway Administration, 49 CFR - Motor Carrier Safety Regulations
Federal Motor Vehicle Safety Regulations and Standards
U.S. Environmental Protection Agency - Federal Energy Administration, 1984 Gas Mileage Guide, California
California Vehicle Code
California Administrative Code
3. Shipping Terms: All prices quoted are to be FOB Destination, no additional Freight charges. Bids quoting otherwise may be rejected.
4. Weight Certificates: If required by DMV to register the vehicle, **weight certificates must be submitted by the vendor upon final delivery of the vehicle.**
5. Fuel: **Each vehicle shall be delivered with a full tank of manufacturer's recommended fuel.**
6. Licensing and Registration: The County may elect to register vehicles supplied under this bid. In this case, the seller shall provide ownership documents, free and clear. In the event that the County elects to have the seller provide vehicle registration service, the seller will provide this service with no additional fees. In this case, the County will provide an exact registration address on the Purchase Order.
7. Warranty: Standard manufacturer's warranties are to be provided and listed for each vehicle. The County's established preventive maintenance procedures and practices shall be accepted in lieu of the manufacturer/dealer's prescribed procedures. This provision shall also apply to any extended warranties.

Special body and equipment warranties shall be a minimum of one year from date of acceptance and include all parts and labor.

All of the above mentioned warranty literature shall be included with the vehicle at the time of delivery.

Warranty offers are important and may be considered in the evaluation of the bids.

County of San Luis Obispo Invitation to Bid #3554-11 December 12, 2011 Page 7
NEW AND UNUSED DUMP TRUCK

8. Manufacturers Literature: One copy of the vehicle owners/operators manual, any other instructions for operation and any other supporting literature is required for each vehicle.

One copy of equipment operating instructions, a complete and current parts list and all other supporting literature is required for all equipment added to a vehicle.

All of the above mentioned manufacturers' literature shall be included with the vehicle at the time of delivery.

9. Delivery: All units are to be delivered F.O.B. Destination to the Fleet Services Shop, 1355-A Kansas Avenue, San Luis Obispo, CA 93401. Final acceptance of vehicles for conformance with the specifications will be made only by the Fleet Manager. Final acceptance will be made within 20 days of receipt of the vehicles.
10. Three sets of keys shall be furnished with each vehicle. A warranty and Owner's instruction manual shall be furnished with each model group.

FINAL COST TO THE COUNTY

The County will award bids based on the bid cost only. Additional charges will not be accepted nor paid by the County. Smog check fees, destination charges, shipping charges, documentation fees, and dealer prep fees may not be charged by the dealer.

SPECIFICATIONS FOR A TANDEM AXLE 15 YARD DUMP TRUCK

REPLACING: Truck number; 1018
QUANTITY: 1

It is the intent of these specifications to describe a 15 yard capacity, Class 8 Commercial Diesel 6x4 Dump truck suitable as a construction material truck for the demands of the Public Works Department, County of San Luis Obispo. The truck must comply with California emissions standards through 2010. This truck will be used for dumping into paving machines and working on confined county roads so the frame dimensions and turning radius are very important.

The complete truck must be of the latest model and carry the manufacturer's new equipment warranty.

Quality, construction details, performance characteristics and price quotations will be analyzed and the truck which best serves the interest of the county may be purchased. The County specifically reserves the right to reject any or all proposals.

All equipment and accessories shall meet OSHA, Department of Industrial Safety and California Highway Patrol regulations. All equipment and accessories are to be mounted or installed to Society of Automotive Engineers or American Trucking Association standards.

Minor deviations from these specifications may be acceptable provided that the operating capabilities or characteristics of the unit are not adversely affected. **Such deviations are to be noted under "DEVIATIONS" column below and or submitted in writing with the bid submission.**

FRAME and DIMENSIONS:

DEVIATIONS

Frame:	"Resisting Bending Moment" of 2,000,000 in. lbs. Heat Treated Alloy Steel, 120,000 KSI rail 1/4" C-Channel inner frame reinforcement	_____
Wheel base:	208" - approximate.	_____
Cab to axle:	140" - approximate	_____
Overhang	55" = approximate	_____
Capacity:	Manufacturer's gross vehicle weight rating shall be not less than 56,000 lbs. Expected Gross Combination Weight: 80,000 lbs	_____
Trailer Towing:	Provision at end of frame for truck	_____

ENGINE:

Six cylinder diesel not less than 380 HP rating, Engine must meet or exceed 2010 EPA Emission Standards

State Engine &
Rating:

ENGINE CONTINUED:

DEVIATIONS

75 MPH Road speed limit		_____
Cruise control speed limit the same		_____
1450 lb-ft Torque, Approximate		_____
PTO to be interfaced to engine and set to allow a maximum		_____

engine speed of 1500 RPM and a minimum of 800 rpm with PTO engaged.

Maximum idle time = 20 minutes

Automatic derating from high water temp, low oil pressure, or low water level.

Engine equipment shall include:

Engine brake: exhaust brake with variable power settings.

Air cleaner: Heavy duty type.

Radiator: Heavy duty, high capacity

Fuel Filters: Spin on type replaceable on engine, plus a "Racor" fuel/water separator or equal.

Throttle: Electronic dash mounted throttle for up to 1500 RPM.

Hand

TRANSMISSION:

Shall be an Allison HD4500 RDS, five to six speed Automatic Transmission.

With PTO Provision

Transmission shall be of correct capacity for use with supplied engine. The transmission shall be equipped with an eight o'clock position opening for P.T.O. mounting. Unit to be filled with synthetic fluid.

FRONT AXLE and SUSPENSION:

Rating: Not less than 16,000 lbs.

Wheelcut: Not less than 40E to stops.

Shocks: Heavy duty shock absorbers.

Seals: Stemco, oil bath seals, with sight window.

Steering: Power steering.

Springs: A combined capacity of not less than 16,000 lbs. and shall be 4" tapered leaf springs.

REAR AXLES and SUSPENSION:

Two Single speed units of 40,000 lbs. total rating. With a full wheel locking differential controlled by switches on dash.

Ratio: Ratio shall be 5.29:1 -- approximate.

Type: Meritor RT-40-145 or equal.

Suspension: Hendrickson RTE 403, 40,000 lb. capacity extended leaf spring type.

BRAKE SYSTEM:

Front Brakes: 16.5 X 5 Rockwell "Q Plus" style "S" cam

Rear Brakes: 16.5 X 7 Rockwell "Q Plus" -- Minimum

Compressor: Bendix "Tu-Flo 750," 16.5 cfm. -- minimum.

ABS system: Bendix

Brake Drums: Outboard mounted

Air dryer: Desiccant type, spin-on cartridge style, such as "Bendix model AD-IS." Heated (Non spin-on type will not be accepted.)

Slack adjusters: Automatic

NEW AND UNUSED DUMP TRUCK

	stainless steel, exhaust elbows chrome, 45	_____
Fire Extinguisher:	1 5# Dry Chemical Type mounted Outboard of drivers	_____
	Seat	_____
Steering Wheel:	Tilt style	_____
Cab	Grab handles for cab entry both sides	_____
Fuel Tanks:	Single, 100 gallon, steel under left side of cab.	_____
Seats:	Drivers, air cushion, high back, vinyl with lumbar	_____
	Support and inboard driver seat armrest	_____
	Passenger, non suspension, high back, vinyl,	_____
	with tool box underneath.	_____
Air horn:	dual, mounted under cab	_____
Wipers:	Electric windshield wipers, intermittent.	_____
Mud flaps:	Spring mounted removable type.	_____
Interior:	Upholstered door panels, Cab interior	_____
	and head liner, for noise reduction.	_____
	Manifest holder on back wall between seats.	_____
Glass:	Tinted glass all windows including windshield and rear	_____
Trailer kit:	Chassis to come wired for 7 pin trailer plug and	_____
	have air system and lines run to rear for trailer brake use.	_____
Warning Kit:	Triangle Reflector kit, 3 triangles I plastic case	_____
Wet Kit:	Shall be installed on truck	_____

ROCK DUMP BODY:

Reference a "Paramount 15' Elliptical" or equal bed.

Bed: Shall be a fully welded body, 15' long, 7' inside width, with a 15 cubic yard capacity

Fenders: Rear of bed to include fenders covering both rear Wheels with removable mud flaps on the rear, or provisions to fasten the flaps out of the way when attached to a paving machine. The front of each fender shall have a mud flap to protect dirt from being Thrown forward by the wheels.

Design:

Elliptical body with a high lift end gate. The sides and end to be made of 3/16" hi-tensile steel with a 1/4" AR-400 steel floor and top pockets or brackets with full length 2½" x 12" treated wood side boards.

Apron: Rear apron to be full width of bed, 8" long and have approximately 10E of slope. Apron to be mounted with 3-inches between bottom of tailgate and top of slope.

Tailgate: Air actuated, double acting high lift gate, with spreader chains.

Tailgate latch: air operated with an over-center cam mechanism to prevent the tail gate from coming open when material applies pressure against it. Control for the tailgate is to be mounted on dash to the left of the steering column.

Mounting: Bed mounts shall be located to provide maximum legal loading of 12,000 lbs. on the front axle and 38,000 lbs. on rear axles with a uniform load in bed. The floor of the bed shall be not less than 54", above the ground, with truck empty. To allow adequate reach for dumping into paving machines, It is critical that the end of the bed be at least 12" and the end of

NEW AND UNUSED DUMP TRUCK

apron not less than 20", beyond the bed hinge.

Cab Shield: A ¼ cab shield is to be mounted at the front of the dump bed to protect cab. The shield and dump bed shall have a minimum of three inches cab clearance.

Step/Crab Handle: Install behind cab, drivers side for access to Look into bed. Handle installed on bed.

Hydraulic System:

Hoist: Telescopic, trunnion mount, Marathon M63138, single 4 stage cylinder, NTEA rated at class 110 minimum. Hoist sub-frame shall be a platform type with weld-on hinges.

Power take off: Shall be a "Muncie" "Hot Shift" PTO mounted as one complete unit to the transmission The PTO shall interface to the transmission and/or engine to cause it to disengage at 1,500 engine RPM's and/or when the vehicle reaches a maximum ground speed of 25 MPH.

Pump: Shall be an air operated " MUNCIE No. E3XA-19-2BPRB" or equal 19 GPM pump. The pump is to be set up for oil circulation back to the tank when not in use, not with internal oil circulation when not in use.

Reservoir: Capacity of at least 20 gallons with sight gauge on tank, shut off valve on supply outlet and a return-line filter.

Controls: Dump and PTO are to be controlled with a pedestal mount air control such as a "Muncie ASC-102" mounted between seats.

Hoses: Supply hose to hydraulic pump shall be at least 1" dia. and all other pressure lines to be at least ½" dia.

Trailer Connections:

Hitch: A heavy duty trailer hitch, "Premier number 2200", Class A, equipped with an air actuated slack adjuster, shall be installed on the rear of the vehicle. -- (No substitute)

Hitch shall be mounted on ends of frame rails and not recessed into frame or mounted in such a manner that any working part of truck may interfere with the normal operation of trailer.

Mounting plate for hitch shall be not more than 24" from center line of rear axle, *the mounting plate should be approximately flush with the rear face of the back tires.* Distance from ground to center of throat of hitch shall be approximately 29 inches.

Air system: Two rigidly mounted standard glad-hand connectors shall be installed on upper left portion of the hitch mounting plate to protect from interference with trailer or dump bed and connected to the truck's brake system through the necessary hose and control valves. Glad hand connectors shall be angled down to prevent the dump apron from hitting when dumping.

"D" Rings: Two heavy duty standard "D" rings shall be

mounted on either side of the pintle hitch to accommodate safety chains for trailer.

ELECTRICAL:

Lighting: California Legal, with lights flush mounted in bed.
To include 2, white Back-up lights.

Trailer plug: A standard seven wire, ABS, electrical connector for trailer plug shall be installed above hitch, in a location that will not interfere with trailer or bed movement.

Warning lights: To include warning lights for dump bed up and PTO engaged.

TOOL BOXES: Highest quality made:

An underbody toolbox shall be mounted to frame under both front sides portion of dump bed. Toolboxes shall be black in color, Approximately 36" Long x 18" Deep x 18" high, with a locking weather tight fold down door.

CRITICAL FACTORS:

Installer should use the following list of critical factors when considering a change in the above specifications. The following factors are of absolute importance to the operation of the truck.

1. The bed must raise under a full load.
2. The tail gate latch must have an over-center latch mechanism to prevent accidental opening of the gate when carrying a load.
3. The bed must operate smoothly with the ability to feather the load slowly up or down.
4. The bed must have a capacity of at least 14 cu. yd's.
5. The bed must have adequate clearance between the exhaust and cab, to prevent contact in actual operating conditions, not just on the shop floor.
6. Controls for operation of the bed must be air type and mounted on a pedestal next to the drivers seat.
7. The bed must extend beyond the chassis enough to allow dumping into a paving machine and not hit the trailer hitch when raised.

MAKE AND MODEL OF:

Dump Bed: _____ Hoist: _____

PTO: _____ Hydraulic Pump: _____

BED TO BE INSTALLED BY: _____

SURFACE TREATMENT & COLORS:

All exposed metal surfaces shall be painted with National School Bus Yellow, Polyurethane or Acrylic Urethane with a clear coat, per FED-STD-595, Acme color No. 85-43350-Y, except that:

Working and/or lubricated joints, cylinders, etc., shall not be painted.

The interior of the engine compartment, and all the underside areas of the vehicle exposed to abrasion from road debris, shall be painted black or have a black permanent undercoating.

Chromium and/or nickel plated surfaces shall not be painted. All other exposed metal surfaces, not readily visible, may be treated or coated with a permanent corrosion preventative, in lieu of painting.

Three sets of keys shall be furnished with vehicle _____

GENERAL:

The unit shall be delivered completely assembled and ready to operate. Upon final delivery, dealer shall provide demonstration of truck operation, safety features and other pertinent information. All equipment cataloged as standard to be furnished and included in purchase price of unit. The component parts of the unit shall be of proper size and design to safely withstand maximum stresses imposed by a capacity load.

Publications: One copy, of the parts books or (CD ROM if available), service manuals, operator's manuals and other pertinent materials covering the entire unit and any added options shall be furnished.

Maintenance Kit: Vendor is to supply 1 complete set of Original Equipment Manufacturers filters for maintenance of truck. The filters are to include, but not be limited to 1 each; Engine Oil Filter, Primary and Secondary Fuel Filter, Coolant conditioner, transmission filters, hydraulic filter

Only the latest models in current production which are cataloged by the manufacturers, and for which manufacturer's published literature and printed specifications are currently available, will be considered.

Bids will be considered only on equipment represented by a reliable manufacturer with a California distributor capable of providing timely service and parts. Dealer shall stock or be able to provide at least 90% of original equipment parts within 48 hours of order. Vendor must be a "Stocking Warranty" dealer within the County of San Luis Obispo or provide proof of a suitable stocking proxy warranty repair station within the County of San Luis Obispo.

An original "**Dealer's Report of Sale**", (not to be replaced by a "Certificate of Origin"), signed by a responsible officer of the vendor with the title of the signer also indicated, shall be furnished promptly to consignee at time of delivery of unit covered by these specifications. Any bill of sale or purchase invoice used by the dealer may supplement but not replace the above.

DELIVERY:

The completed unit shall be delivered to the Fleet Services Shop at 1355A Kansas Avenue, San Luis Obispo Ca. **Any questions regarding delivery or construction details shall be directed to the County Fleet Manager, Scott Wetmore, at 805-781-5288 or 805-440-1125. Contact Scott 24 hours prior to delivery.**

Delivery time of the truck, may be a key consideration in the award of the purchase order. In terms of days based on straight calendar days, vendors are instructed to quote their best delivery time for the truck bid. The truck selected for purchase shall be delivered on or before the number of calendar days quoted by the successful vendor.

Time is of the essence hereof. If the truck is not delivered in the time quoted by the vendor in this bid, or within any period of extension as authorized in writing by the County, it is understood the County will suffer damages from loss of use of said

County of San Luis Obispo Invitation to Bid #3554-11 December 12, 2011 Page 15
NEW AND UNUSED DUMP TRUCK

truck(s); and it being impracticable and infeasible to determine the actual damage, it is agreed that vendor shall pay to the County as fixed and liquidated damages and not as a penalty, the sum of One hundred dollars (\$100.00) for each working day of delay until the truck is delivered and accepted, and vendor shall be liable for the amount thereof, and the County may deduct said sums from any money due or that may become due the vendor; provided, however, that any delays in the delivery of truck due to unforeseeable causes beyond the control and without fault or negligence of the vendor (including but not limited to: act of County, fires, floods, epidemics, quarantine restrictions, strikes, or freight embargos).

Vendor shall, within five (5) calendar days from the beginning of any such delay, notify the County in writing of the cause of the delay; whereupon the County shall ascertain the facts and the extent of the delay and extend the time for delivery of the unit, when in it's judgment the findings of facts justify such an extension of delivery. The County's findings of fact thereon shall be final and conclusive on the parties hereto.

A weight certificate for complete vehicle shall be provided at time of delivery.

WARRANTY:

The cab and chassis is to come with an additional extended warranty. This warranty is to cover all power-train components, and cab components as indicated below. The County would prefer a minimum of three years warranty on all components if available. The base warranty for the engine should be at least 5yr /100,000mi.

List below the Basic warranty and the extended warranty available along with the cost for the extended warranty indicated:

	Length of warranty coverage	Cost
Cab and chassis;		
Basic Warranty	_____	
Extended Warranty	_____	_____
Engine;		
Basic Warranty	_____	
Extended Warranty	_____	_____
Transmission;		
Basic Warranty	_____	
Extended Warranty	_____	_____
Differential;		
Basic Warranty	_____	
Extended Warranty	_____	_____

County of San Luis Obispo Invitation to Bid #3554-11 December 12, 2011 Page 16
NEW AND UNUSED DUMP TRUCK

The undersigned agrees to:

Deliver FOB San Luis Obispo to Fleet Services, 1355-A Kansas Avenue, San Luis Obispo, CA 93401, the vehicles itemized below and in accordance with the Specifications attached. All equipment to be new and unused of the latest model year and all attachments shall be compatible with the vehicles proposed.

All equipment and accessories shall comply with the applicable State and Federal Codes, Regulations and Requirements.

Equipment shall be delivered serviced and ready to operate and in accordance with the vehicle checklist.

Bid Summary

ITEM	SPEC	QUANTITY	UNIT COST	7.25 % SALES TAX	MAKE & MODEL BIDDING	TOTAL BID PRICE
1	A	1 each Dump Truck	\$ _____	\$ _____	_____	\$ _____
2	Full Extended Warranty As Specified		\$ _____	N/A	N/A	\$ _____
GRAND TOTAL						\$ _____

PAYMENT TERMS: _____

DATE OF DELIVERY: _____

Authorized Official Name (Print) _____

Authorized Official Title (Print) _____

Signature _____

Firm Name _____

Address _____

City _____ State _____ Zip Code _____

Telephone _____ FAX _____

Federal Taxpayer ID# _____

BIDS **MUST** BE RECEIVED BY 3:00 P.M., **JANUARY 4, 2011** AND
 WILL BE OPENED IN THE OFFICE OF THE GENERAL SERVICES AGENCY
Bid #3554-11

**GENERAL SERVICES AGENCY COUNTY GARAGE
 VEHICLE INSPECTION CHECKLIST**

NEW VEHICLES WILL NOT BE ACCEPTED UNTIL THE CONTRACT VENDOR HAS PERFORMED THE PRE-DELIVERY SERVICE ON THE VEHICLE IN ACCORDANCE WITH THIS LISTING OR OTHER INDUSTRY APPROVED CHECKLIST.

<p><u>UNDER HOOD – ENGINE OFF</u></p> <p>Engine oil level; Steering gear housing fluid level; Brake master cylinder fluid level; Radiator coolant level; Battery fluid level; Drive belt tensions; Battery voltage & load-voltage drop; Ignition system; Fuel injection system.</p>	<p><u>ON INSIDE</u></p> <p>Operation of lights, turn signals, stop signals, horn, courtesy lights, oil pressure & alternator warning lights; Front seat control-Operation (manual or power); Station wagon rear seat & floor - operation; Windows & vents-operation & fit; Glass condition; Cigarette lighter-install & test.</p>
<p><u>UNDER HOOD – ENGINE OPERATING</u></p> <p>Automatic transmission fluid level.</p>	<p><u>ON HOIST – OR UNDERSIDE</u></p> <p>Axle fluid level; Hydraulic lines, fittings, connections & components on underside for leaks; Tire pressure; Steering linkage & connections.</p>
<p><u>UNDER HOOD – ENGINE OPERATING & HOT</u></p> <p>Initial ignition timing; Alternator & voltage regulator operation.</p>	<p><u>ALIGNMENT STALL</u></p> <p>Front wheel toe-in.</p>
<p><u>OTHER OPERATIONS</u></p> <p>Engine cold and hot idle speeds; Hydraulic lines, fittings, connections & components for leaks; Fuel system for leaks.</p>	<p><u>ROAD TEST</u></p> <p>Neutral switch-operation (automatic transmission); Parking brake-operation; Horn, windshield wipers & washers-operation; Heater & air vents-operation; Brake-operation; Transmission shift level-operation; Automatic transmission shift timing & quality; Accelerator pedal-operation; Engine performance; Drive belts; Steering control; Squeaks, rattles & wind noise; Speedometer, odometer, fuel & temperature gauge-operation; Other operational equipment-operation.</p>

GENERAL SERVICES AGENCY COUNTY GARAGE
VEHICLE INSPECTION CHECKLIST

<u>ON OUTSIDE</u>	<u>AFTER ROAD TEST</u>
Latches, keys & locks-operation; Hand, deck & door panels for fit & alignment; Bumpers & moldings-alignment; Weather strips-adhesion & fit; Wheel nut torques; Five gallons of fuel in fuel tank.	Wash vehicle & check for leaks; Inspect for interior & exterior metal paint damage; Check soft trim for soilage & excess sealer.

Vehicle warranty shall be the standard warranty furnished by the manufacturer of the vehicle supplied. All vehicles covered by factory warranty shall be corrected by contractor, or any factory authorized dealer for that vehicle, at cost to the agency.

The checklist was completed by:

VENDOR NAME: _____

VENDOR EMPLOYEE NAME: _____

DATE: _____

FOR VEHICLE MAKE & MODEL: _____