



# SELF-VERIFICATION FOR SMOKE DETECTORS, CO ALARMS AND PLUMBING FIXTURE RETROFIT

PLANNING & BUILDING DEPARTMENT • COUNTY OF SAN LUIS OBISPO  
976 OSOS STREET • ROOM 200 • SAN LUIS OBISPO • CALIFORNIA 93408 • (805) 781-5600

I, \_\_\_\_\_, owner of the dwelling located at:  
(Print Property Owner's Name)

\_\_\_\_\_  
(Print Address)

verify that the smoke and carbon monoxide (CO) alarms required by the California Residential Code (CRC) have been installed in the dwelling, in compliance with the CRC and with the manufacturer's instructions and further that they have been tested and do function properly. These alarms enhance life safety within dwellings. CRC Section R314 and R315 require the retrofit of these alarms in existing dwellings when alterations, repairs or additions requiring a permit with a valuation exceeding \$1,000 are made. Generally, the alarms must be hard wired (110 volt) with battery back-up and all alarms are to be interconnected. If the installation of the alarms will require the removal of wall or ceiling finishes or there is no access by means of attic, basement or crawl space, then alarms may be solely battery operated and not interconnected but such battery-only type smoke alarms must be equipped with a 10 year battery and have a silence feature. Alarms must be installed in all of the following locations within the existing dwelling and must be no more than 10 years old (from the date of manufacture as marked on the unit – units without a date of manufacture identified must be replaced):

- In all bedrooms (only require Smoke Alarms)
- Immediately outside and in the immediate vicinity of each bedroom area (require Smoke and CO Alarms)
- In each story level, including basements and habitable attics (require Smoke and CO Alarms)

In addition, I (the property owner) also verify that all plumbing fixtures within the dwelling unit are in compliance with the applicable retrofit provisions of California Civil Code Section 1101 and the Water Conservation Implementation Plan for the Los Osos Wastewater Project, which requires that the existing fixtures do not exceed the flow rates stated:

- Toilets – not more than 1.6 gallon of water per flush (if replaced - 1.28 gpf)
- Urinals – not more than one gallon of water per flush (if replaced - .5 gpf)
- Showerheads – not more than 2.0 gallons of water per minute (if replaced – 1.5 gpm)
- Residential faucets – not more than 1.5 gallons of water per minute
- Commercial Faucets – not more than 0.5 gallons of water per minute

I have read and understand the above requirements and affirm by my signature, that all required alarms mentioned above have been properly installed and tested and that the plumbing fixtures mentioned above are in compliance with the applicable water conservation requirements of California Civil Code Section 1101.

\_\_\_\_\_  
Signature of Property Owner

\_\_\_\_\_  
Date

*Note: County of S.L.O. Building Inspector is still allowed to verify the above requirements prior to final.*